

Avery Weigh-Tronix



WP-233 Dot Matrix Impact Printer

Features and benefits

- RS-232
- Small enough (4½" x 4" x 2") to fit anywhere—Table top, wall, or panel mounting available.
- 24-, 32-, and 40-column printing capacity
- Uses standard 2½" adding machine paper
- Programmable double high and/or double wide characters
- Easily replaceable black cartridge.
- Dual function rocker switch: On/Standby, Paper feed
- Available in AC or DC models.
- Optional watertight enclosure available.
- X-ON, X-OFF and Busy Signal-clear to send (CTS) are both supported.
- Selectable sequential transaction number printing

Specifications

Print method: Impact dot matrix

Character matrix: 5 x 8 or 5 x 5 matrix

Character spacing:

24 column - 12.8 characters/inch
32 column - 17 characters/inch
40 column - 21 characters/inch

Line feed spacing:

7.6 lines per inch...single high character mode

Character buffering: 1.5K or 9.5K

Paper roll:

Table top - 2¼" W x 2½" O.D.; 0.44" I.D.
Panel mount - 2¼" W x 1¼" O.D.

Power: 1.5 Watts (idle) 10 Watts (while printing)

AC voltage: 9 VAC (120 VAC stepdown converter included)

DC voltage:

Optional 9-12 VDC, 100 mA idle, 1.5 A typical, 2.9A peak
Optional 12-48 VDC

Available baud rates:

300, 600, 1200, 2400, 4800, 9600, 19200

Character format:

7, 8 data bits, 1 or 2 stop bits, even, odd or no parity


Environment: 5°C to 40°C (41°F to 104°F)

Shipping weight: 3 lbs


Options:

Time/date battery protected circuitry
Wall mounting versions and a watertight enclosure are available, for both AC and DC models.

AC, 9-12 VDC version dimensions



12-48 DC version dimensions



Avery Weigh-Tronix



Avery Weigh-Tronix
1000 Armstrong Dr.
Fairmont, MN 56031 USA
Telephone: 507-238-4461
Facsimile: 507-238-4195
e-mail: industrial@weigh-tronix.com
www.wtxweb.com

Avery Weigh-Tronix Canada, ULC
217 Brunswick Boulevard
Pointe Claire, QC H9R 4R7 Canada
Telephone: 514-695-0380
Toll free: 800-561-9461
Facsimile: 514-695-6820
www.weigh-tronix.ca